

# Converting Hydrocarbons to Recyclable Materials for Metal Replacement with Positive Hydrogen Output

Matteo Pasquali, Rice University

Glen Irvin, Boris Yakobson, Evgeni Penev, Rice University

Joe Trentacosta, JDT LLC

Leonardo Spanu, John Lockemeyer, Sander van Bavel, Shaojun Miao, Carl Mesters\*,

Joe Powell\*, Shell

Matteo Maestri, Politecnico di Milano

Jeff Blackburn, NREL


Decarbonizing the industrial sector and lightweighting transportation by making lightweight structural materials and conductors via co-production of advanced carbon materials and clean hydrogen

Total project cost: \$3.45M

Length 36 mo.

# A novel hydrocarbon pathway: materials with structural integrity






## Valuation of carbon vs. hydrogen co-products: Carbon First



https://www.pnas.org/content/118/31/e2112089118 Pasquali and Mesters, PNAS 2021









# **POLITECNICO** DI MILANO



Evgeni Penev





Glen Irvin



Leonardo Spanu




Shaojun Miao



Matteo Maestri









Joe Trentacosta



John Lockemeyer



Sander van Bavel





**Boris Yakobson** 

Joe Powell\*

Carl Mesters\*

# **Program Flow**






Taylor et al, Carbon, 2021







https://www.sciencedirect.com/science/article/abs/pii/S0008622320307193


Spec. Electrical Cond. [Sm<sup>2</sup>/kg]


Materials properties level

## **CNT** synthesis: productivity improvements in 2021










#### **Economics & current efforts**


- High dilution (being reduced)
- Flow patterns (redesigning injection)
- Process intensification

Collaboration with S. M. Kim's group (KIST)

#### **CNT synthesis: property improvements in 2021**









• In-house production (0.4-0.5 g/hr) is now sufficient for spinning CNT fibers comparable to SoA properties

#### **CNT fiber spinning: improvements in 2021**







Note: current process development with partner's mid-quality CNTs

Spinning @ 10wt%, Gen2 Line, In-line and Post-Stretch Capabilities Deployed

Microstructure Development & Scaling

Overall Program deliverables

CNT Synthesis Process Efficiency and Scaling

\$/kg

#### **Achievements, Challenges and Potential Technical Partnerships**

#### **Achievements**

- Synthesis: demonstrated concurrent
  - mid-throughput production
  - high CNT selectivity & quality (translated into fibers)
- Can estimate process thermodynamic efficiency
- Spinning: demonstrated
  - high-throughput production
  - major process intensification via high concentration spinning
  - CNT fiber properties maintained at high throughput

#### **Biggest Challenges**

- Increase methane concentration in feedstock
- Increase methane conversion (keeping selectivity)
- Decouple reaction and reactor
- "Killer app(s)"

#### Risk Reduction Approaches


- Two catalyst delivery systems; in-line catalyst measurement & gas-phase analysis
- Flow distribution system redesign to decouple transport and kinetics
- Collaborations for source CNTs
- Collaborations for application development

#### Partnerships and collaboration opportunities

- carbonhub.rice.edu
- Application development: we can provide material and expertise
- CNT material conversion: we can (try to) make fibers, tapes from other's CNTs

COI: MP owns equity in DexMat

Hub



Collaboration with DexMat, Inc. <a href="https://dexmat.com/">https://dexmat.com/</a>





#### **T2M:** Grid Transmission Overhead Power Lines

Multiple functionalities: strength, lightweight, electrical & thermal conductivity

Grid transmission conductors require multiple functionalities

- Specific electrical & thermal conductivity
- Specific strength for long spans
- Market opportunity: ~3 Tons/mile (high voltage)
- Opportunity to simplify system design, lowering Total Cost of Ownership








Taylor et al, Carbon, 2021

https://doi.org/10.1016/j.carbon.2020.07.058



# Collaboration with Prysmia

© Rice University 2022. All rights reserved.